

MB42x72 JSS



Features:

Portable plastic barricade is ideal for perimeter delineation, crowd control, construction sites, and parking areas. Lighter and more easily deployed than concrete road barriers, the heavy-duty unit is fabricated to ballistics testing requirements. Extremely durable, once positioned, barricades are very difficult to move. Typical deployments include security, gate access, traffic control approaches, stand-off zones, perimeter/boundary lines, and hazardous material spills. Live fire tests have been conducted on .35" wall polyethylene barriers by HP White Labs.

Specifications:

- Can be set up to create an interconnected wall with no gaps.
- Vandal-proof U-connector system has the capability of locking in such a manner that prevents repositioning once set up.
- Wall thickness of .375" or greater. Meets ballistic testing requirements.
- Available in approved OSHA safety colors.
- System provides structural integrity for anti-ramming.

Optional Accessories:

- Our plastic Jersey Style barricades use a patented locking device, the U-connector to keep barricades from being forced apart.
- Stanchions can be utilized with snow fencing or used with barricade rail to create Type III barricade.
- Pre-molded attachment area for flashing lights.
- Compatible with Multi-Barrier model MB42x96 JSS.



COLORS:

Orange, white, custom colors

COMPOSITION:

High impact, UV resistant, polyethylene made of resiliently deformable and non-conductive materials.

SIZE:

Height: 42" / 106.6 cm
Length: 72" / 182.8 cm
Width: 24" / 60.9 cm
Reg. Wall: .25" / 6.35 mm
HD Wall: .35" / 8.9 mm
SHD Wall: .50" / 12.7 mm

WEIGHT:

Reg: Empty: 100 lbs / 45.3 kg
Full: 1380 lbs. / 625.9 kg
HD: Empty: 130 lbs. / 58.9 kg
Full: 1410 lbs. / 639.5 kg
SHD: Empty: 170 lbs. / 77.1 kg
Full: 1450 lbs. / 657.7 kg

WATER BALLAST:

153 gallons / 579 liters



NSN #566-01-4669-5339 Yellow
NSN #566-01-4669-5340 Desert Tan
NSN #566-01-4669-5341 Orange
NSN #566-01-4669-5342 White
NSN #566-01-4669-5343 Olive Drab